


## Mix60 Duo Fixed Trim

TM65.2 3kgCO2e

TM66 2.5 CEAM



Ø62mm (2,44") overall trim, Ø35mm (1,39") aperture. Available with a standard trim kit or 3 flush trim options, depending on ceiling type and finish.

Mix60 Duo with Trim Kit TR1<sup>(1)</sup>

Cut-out Ø 56mm

Required depth height +15mm.

LED Source	LED35/3-WD	LED35/3-WD	LED35/3-WD
CRI	≥90 CRI	≥90 CRI	≥90 CRI
Drive Current	350mA	350mA	350mA
Power inc Driver	7.4W	7.4W	7.4W
Beam Angle	NF (21°)	FL (37°)	WFL (46°)
Forward Volt	18V	18V	18V
CCT	2700K 3000K	2700K 3000K	2700K 3000K
Delivered Lumens	489 540	458 513	407 452
Delivered Intensity cd	2766 2935	1126 1208	645 684
Delivered Lumens per circuit watt	66 73	62 69	55 61

Note: Performance data is based on the Highest CCT of each module type.

Project Ref: \_\_\_\_\_

Location Ref: \_\_\_\_\_

Please only complete one of the following code builders

## Non Fire Rated Code Builder

Fixture Order Code: **MX60000-DU** –  –  –  – **0**Fixture  
MX60000-DU Mix60 Duo Fixed for LEDInstallation <sup>(1)</sup>  
TR1 <sup>(2)</sup> Trim for Existing Ceilings 5-15mm total thickness  
TR2 Trim for Existing Ceilings 15-28mm total thicknessFinish  
WH02 White RAL 9010  
BK02 Black RAL 9005  
RAL\* Custom RAL Colour\*  
ABR1 Antique Brass  
ABZ1 Antique Bronze  
PCH1 Polished Chrome  
PNK1 Polished Nickel  
PBR1 Polished BrassIP Rating  
54 IP54  
65 IP65Rating  
0 No Fire Rating

## Fire Rated Code Builder

Fixture Order Code: **MX60000-DU** – **TR2** –  –  – **FR**Fixture  
MX60000-DU Mix60 Duo Fixed for LEDInstallation <sup>(1)</sup>  
TR2 <sup>(2)</sup> Trim for Existing Ceilings 15-28mm total thicknessFinish  
WH02 White RAL 9010  
BK02 Black RAL 9005  
RAL\* Custom RAL Colour\*  
ABR1 Antique Brass  
ABZ1 Antique Bronze  
PCH1 Polished Chrome  
PNK1 Polished Nickel  
PBR1 Polished BrassIP Rating  
54 IP54  
65 IP65Rating  
**FR** <sup>(3)</sup> Fire Rated<sup>(1)</sup> For any ceiling thickness or construction type not shown please contact Lucent<sup>(2)</sup> Adjustment may be limited in thicker ceiling constructions. Refer to installation instructions for details.<sup>(3)</sup> Tested and approved to EN 1363-1:2020 and EN 1365-2:2014 for 60 minutes fire rating.

Project Ref: \_\_\_\_\_

Location Ref: \_\_\_\_\_

LED Order Code:

LED  
LED35/3-WDCCT  
2718  
3018Beam  
NF  
FL  
WFL

[LED35/3-WD] - [ ] - [ ]

LED35 Gen3 Ambiance WarmDim

2700K - 1800K  
3000K - 1800KNarrow Flood  
Flood  
Wide Flood

Driver Options:

Protocol

S Non-Dim  
A Analogue (0-10v)  
P Phase  
D DALI  
B Bluetooth\*\*


[ ]

Emergency Options:

Emergency

E Maintained 3hr Emergency  
ED Maintained 3hr DALI Self Test  
ES Maintained 3hr Self Test

## Finish selection



Antique Brass



Antique Bronze



Polished Brass




Polished Nickel




Polished Chrome

## Accessories




Honeycomb Louvre



Diffusing Lens



Frosted Lens



Heavy Spread Lens



Linear Spread Lens

Accessories Order Code:

Louvre/Lens	_____
LS45	Honeycomb Louvre
LSDF	Diffusing Lens
LSFR	Frosted Lens
LSLS	Linear Spread Lens
LSHS	Heavy Spread Lens

## Technical Details

\*Custom RAL code must be specified. Custom RAL colours can increase prices and lead times

Dimming. Whilst Lucent can offer the majority of its luminaires with various dimming options, it remains the responsibility of the specifier/installer to check and ensure compatibility of any control equipment used. Additional cabling may be required depending on the dimming protocol specified.

\*\*Bluetooth (wireless) is the communication method. The exact dimming protocol must be confirmed to allow the selection of suitable drivers or bluetooth devices.

^ Depth indicated is the minimum recess depth for the luminaire with a remote mounted LED driver. Installing a driver through either the luminaire cut-out or installation kit may require additional recess depth, please refer to the relevant luminaire installation instructions for further details. Data correct at time of publishing

First Fix Requirement. Luminaire comprised of fixture body with ceiling trim and installation kit, which is to be fitted into the ceiling once finished. Ensure correct alignment of the installation kit before final assembly (see luminaire installation instructions for details)

IP Rating. Tested from underside of the ceiling

Note that the picture of the finishes provided is for illustrative purposes only. The finishes may vary in colour, texture and appearance. Contact Lucent lighting Ltd for more information.

It is the policy of Lucent Lighting to continually review and improve its products and therefore reserve the right to change any details of product or withdraw specifications without prior notice.

Luminaires designed to comply with EN60598 and all other standards.

This specification sheet supersedes all previous versions.

All intellectual property rights pertaining to the product described above and to this document are owned by or licensed to Lucent Lighting Ltd.

We reserve the right to take whatever action is necessary to protect those intellectual property rights.