

ProSpex Edge90 Fixed


TM65.2	13kgCO2e
TM66	2.3 CEAM



92mm (3.62”) overall diameter. Edge baffle to ensure aperture is glare free and for a professional look. Available with standard trim kit or plaster-in kit for flush appearance. Family of matching products also available.



91413-A-LED + 9000-PBZ
Cut-out Ø83mm
Trim kit
Required depth height+15mm^



91413-A-LED + 9000-PCZ
Cut-out Ø83mm
Seamless flush appearance
Required depth height+15mm^

LED Source	LED51/3-SL	LED51/3-SL	LED51/3-SL	LED51/3-SL
CCT	3000K	3000K	3000K	3000K
Drive Current	200mA	200mA	200mA	200mA
Power inc Driver	8.5W	8.5W	8.5W	8.5W
Beam Angle	SP (12°)	MF (19°)	FL (30°)	WFL (52°)
Delivered Lumens	490	519	628	618
Delivered Intensisty cd	6999	3874	2291	912
Efficacy lm/w	58	61	74	73
Forward Volt	36V	36V	36V	36V
CRI	≥90 CRI	≥90 CRI	≥90 CRI	≥90 CRI

Apply these factors to 3000K for lumen output of other CCTs: **2200K** x 0.65 / **2400K** x 0.69 / **2700K** x 0.98 / **4000K** x 1.02.

Copyright © 2025 Lucent Lighting Ltd.

Project Ref:_____ Location Ref:_____

Fixture Order Code: 91413-F-LED – [ ] – [ ]


Fixture
91413-F-LED	Edge90 Fixed with LED51

Finish
WH	White RAL 9010
BK	Black RAL 9005
RAL*	Custom RAL Colour*
ABR1	Antique Brass
ABZ1	Antique Bronze
PCH1	Polished Chrome
PNK1	Polished Nickel
PBR1	Polished Brass

IP Rating
(Blank)	IP20
54	IP54
65	IP65

Installation Order Code: [ ]

Installation
9000-PBZ	Trim kit for trimmed appearance
9000-PCZ	Plaster-kit for seamless flush appearance



Module Order Code: LED51/3 – [ ] – [ ] – SL

LED
LED51/3	LED50 ONE GEN3

CCT
22 (3)	90 CRI 2200K
24 (3)	90 CRI 2400K
27	90 CRI 2700K
30	90 CRI 3000K
40 (3)	90 CRI 4000K

Beam
SP	Spot
MF	Medium Flood
FL	Flood
WFL	Wide Flood

Ouput Type
SL	Shallow Height, Low ouput

(3) contact Lucent for availability

Driver Options: [ ]

Protocol
S	Non-Dim
A	Analogue (0-10v)
P	Phase
D	DALI
B	Bluetooth**

Emergency Options: [ ]

Emergency
E	Maintained 3hr Emergency
ED	Maintained 3hr DALI Self Test
ES	Maintained 3hr Self Test

Copyright © 2025 Lucent Lighting Ltd.

Finish selection




Antique Brass



Antique Bronze



Polished Brass



Polished Nickel




Polished Chrome

Accessories




Honeycomb Louvre



Diffusing Lens



Frosted Lens



Heavy Spread Lens



Linear Spread Lens

Accessories Order Code:

Louvre/Lens
LL45 Honeycomb Louvre
LLDF Diffusing Lens
LLFR Frosted Lens
LLLS Linear Spread Lens
LLHS Heavy Spread Lens

Copyright © 2025 Lucent Lighting Ltd.

Technical Details

*Custom RAL code must be specified. Custom RAL colours can increase prices and lead times

Dimming. Whilst Lucent can offer the majority of its luminaires with various dimming options, it remains the responsibility of the specifier/installer to check and ensure compatibility of any control equipment used. Additional cabling may be required depending on the dimming protocol specified.

**Bluetooth (wireless) is the communication method. The exact dimming protocol must be confirmed to allow the selection of suitable drivers or bluetooth devices.

^ Depth indicated is the minimum recess depth for the luminaire with a remote mounted LED driver. Installing a driver through either the luminaire cut-out or installation kit may require additional recess depth, please refer to the relevant luminaire installation instructions for further details.Data correct at time of publishing

First Fix Requirement. Luminaire comprised of fixture body with ceiling trim and installation kit, which is to be fitted into the ceiling once finished. Ensure correct alignment of the installation kit before final assembly (see luminaire instllation instructions for details)

IP Rating. Tested from underside of the ceiling

Note that the picture of the finishes provided is for illustrative purposes only. The finishes may vary in colour, texture and appearance. Contact Lucent lighting Ltd for more information.

It is the policy of Lucent Lighting to continually review and improve its products and therefore reserve the right to change any details of product or withdraw specifications without prior notice.

Luminaires designed to comply with EN60598 and all other standards.

This specification sheet supersededs all previous versions.

All intellectual property rights pertaining to the product described above and to this document are owned by or licensed to Lucent Lighting Ltd.

We reserve the right to take whatever action is necessary to protect those intellectual property rights.

Please notify Lucent Lighting Ltd of any inaccuracies immediately. E&OE