

## Light efficiency:


**63 Lumen/Watt**

## Light quality:

**CRI: 91.6**

## Color temperature:

**3000 K**



## Product name:

**TubeLED Mini GEN2  
3000K 24° 350mA**


## Item number:

**7100/2-30-24-350mA**


**Delivered information for  
above fixture and LED  
combination.**

**Output: 852 Lumen   Peak intensity: 5551 cd   Power consumption: 13.6**


## CRI R values



## TM30 C Values




## Color vector graphics



Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
3000 K	91.6	57.5	91.3	99.3	90.2	0.437	0.404	0.251	0.348	0.0011

## Beam details



## Beam angels

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%
19.6°	36.9°	54.8°

## Beam intensities

Peak intensity	Int. ratio in 120° cone	Int. ratio in 90° cone
5551 cd	99.3%	98.5%

## Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
5551lx	1388lx	617lx	347lx	222lx	154lx	113lx	87lx	69lx	56lx	46lx	39lx	33lx	28lx	25lx	22lx	19lx	17lx	15lx	14lx
515.7fcd	128.9fcd	57.3fcd	32.2fcd	20.6fcd	14.3fcd	10.5fcd	8.1fcd	6.4fcd	5.2fcd	4.3fcd	3.6fcd	3.1fcd	2.6fcd	2.3fcd	2fcd	1.8fcd	1.6fcd	1.4fcd	1.3fcd

The above information is for 3000K colour temperature, for specific module information please see LED spec located on our website

For information regarding other colour temperatures please use the following factors for lumen output and candelas:

2700K = 1

4000K = 1.084