


Light efficiency:



Light quality:



Color temperature:



Product name:

TubeLED Mini SuperSpot, 3000K, 7°, 1000mA


Item number:

7100/SS-930-7-1000mA


Delivered information for above fixture and LED combination.

Output: 722 Lumen Peak intensity: 26123 cd Power consumption: 12.3W


CRI R values



TM30 C Values




Color vector graphics



Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
3069 K	90.9	50.7	91.2	99.0	89.5	0.433	0.403	0.248	0.347	0.0003

Beam details



Beam angles

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%
7.6°	13.5°	20.9°

Beam intensities

Peak intensity	Int. ratio in 120° cone	Int. ratio in 90° cone
26123 cd	95.0%	93.6%

Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
26123lx	6531lx	2903lx	1633lx	1045lx	726lx	533lx	408lx	323lx	261lx	216lx	181lx	155lx	133lx	116lx	102lx	90lx	81lx	72lx	65lx
2426.9fcd	606.7fcd	269.7fcd	151.7fcd	97.1fcd	67.4fcd	49.5fcd	37.9fcd	30fcd	24.3fcd	20.1fcd	16.9fcd	14.4fcd	12.4fcd	10.8fcd	9.5fcd	8.4fcd	7.5fcd	6.7fcd	6.1fcd

The above information is for 3000K colour temperature, for specific module information please see LED spec located on our website

For information regarding other colour temperatures please use the following factors for lumen output and candelas:

2700K = 0.9